55 Stafford Court Cambridge, ON N1T 1B3

P (519) 623-7448 F (519) 623-8807

COMMIX 37 SERIES

High Efficiency Liquid-Liquid Coalescers

- **Absolute Rated**
- 0.5, 2, 5, 10, 20 and 40 Micron Available
- Inside to Outside Flow Path

Commix 37 filters offers excellent coalescing efficiency, capacity and contaminant removal and prevents unexpected shut downs.

SUITABLE USES





Air & Gas

MEDIA

EFFICIENCY

99.98%

SIZING Available in 20" and 40" lengths with a 3.75" OD

Additional sizes available, please contact Fil-Trek

Microglass, Polyester, Nylon or ECTFE

ADDITIONAL FEATURES

Standard open end configuration

COMMON APPLICATIONS Water removal from diesel, gasoline, kerosene, LPG, hydrocarbon condensates, LPG, NGL, chemicals, etc

Water removal from OII removal/recovery from water streams

Amine removal from hydrocarbons

Hydrocarbon removal from quench water

Caustic removal from fuels

For more information, e-mail: info@fil-trek.com or visit Fil-Trek.com

COMMIX 37

High Efficiency Liquid-Liquid Coalescer

- Absolute Rated
- 0.5, 2, 5, 10, 20 and 40 Micron
- Inside to Outside Flow Path



ELEMENT SPECIFICATIONS

REC. DIFFERENTIAL PRESSURE	15 PSID
REC. FLOW RATE	Subject to application, please contact factory
MAX. OPERATING TEMPERATURE	300°F (148.9°C)
MICRON RATINGS	0.5, 2, 5, 10, 20, 40

DIMENSIONAL DETAILS

MODEL	OD	LENGTH
CX37-20	3.75	20"
CX37-40	3.75	40"

Additional sizes available, please contact Fil-Trek.

MATERIAL OF CONSTRUCTION

Media	Microglass, Polyester, Nylon or ECTFE
Support Structure	SS304
End Caps	SS304
Gaskets	Buna-N (std) EPDM Viton
FILTER CONFIGURATION	Open ends (std)



PRODUCT NOMENCLATURE

CX37	2	S4	MG	40		VI
MODEL	MICRON	NON-MEDIA COMP.	MEDIA	LENGTH	END CAP	O-RING/SEAL
CX37 - Commix 37	0.5	S4 - SS304	MG - Microglass	20 - 20"	Blank - Open Ends	BN - Buna-N
Series	2		PE - Polyester	40 - 40"		EP - EPDM
	5		NY - Nylon			VI - Viton
	10		HA - ECTFE			
	20					

For more information, e-mail: info@fil-trek.com or visit Fil-Trek.com

